


Product Code

**3065/6C**

Safety Valve

3/4"NPTx1"G Pset=60,0bar<br>PS = 70 bar



**G GREEN**

STABILIZZAZIONE DEL FLUIDO

**P LYHEDRA**

**CL ASSIC**

## Product use

Safety valve series 3030, 3060, 3061 3065, 3030E and 3061E, unbalanced conventional direct load. The valve opens when the thrust exerted on the plunger by the refrigerant under pressure, under calibrated conditions, overcomes the opposing force of the spring acting on the plunger.

Safety accessories for use with refrigerant R744, belonging to Group 2 as defined in Article 13 of Directive 2014/68/EU. Calibration range:

- from 9 to 50 bar for series 3030 and 3060
- from 11 to 60 bar for series 3061 and 3065
- from 60 to 150 bar for series 3030E and 3061E

## Product Details

**Connections IN** 3/4" NPT

**Connections OUT** 1" G

**Orifice section [mm<sup>2</sup>]** 132,7

**Discharge coefficient Kd** 0,87

**Set pressure range [bar]** 11 - 60

**PS[bar]** 70

**TS[°C] min.** -50

Castel non si assume alcuna responsabilità per eventuali errori nei cataloghi, opuscoli e altro materiale stampato o indicato nel sito Castel.it. Castel si riserva il diritto di modificare i propri prodotti senza preavviso. Tutti i marchi in questo materiale sono di proprietà di Castel. Tutti i diritti riservati.

Castel assumes no responsibility for any errors in catalogs, brochures and other material printed or indicated on the Castel.it website. Castel reserves the right to modify its products without notice. All trademarks in this material are the property of Castel. All rights reserved.

TS[°C] max.	+150
-------------	------

Package pcs	24
-------------	----

Notes where expressly stated