# Product Code

# DF305EX/M10S

Solid Core Filter Drier ATEX
10mm ODS<br>PS = 47 bar




## Product use

Hermetic filter dryers with the ?EX? suffix are compliant with the ESR of Directive 2014/34/EU ? ATEX. This equipment is suitable for use on refrigeration systems located in areas classified as ?Zone 2? risk of explosion, according to the definition in Annex I of Directive 1999/92/EC.
Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:
HFC (R134A, R32, R404A, R407C, R410A, R507)
HFO (R1234YF, R1234ZE)
HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)
HC (R290, R600, R600A, R1270)

## Product Details

| | |
|---|---|
| **International code** | - |
| **Connections ODS Ø [in.]** | - |
| **Connections ODS Ø [mm]** | 10 |
| **ODM Ø [in.]** | - |
| **ODM Ø [mm]** | 12 |
| **Nominal volume [cm³]** | 80 |
| **PS [bar]** | 47 |
| **TS [°C] min.** | -40 |
| **TS [°C] max.** | +150 |
| **Package pcs** | 25 |

*Castel non si assume alcuna responsabilità per eventuali errori nei cataloghi, opuscoli e altro materiale stampato o indicato nel sito Castel.it. Castel si riserva il diritto di modificare i propri prodotti senza preavviso. Tutti i marchi in questo materiale sono di proprietà di Castel. Tutti i diritti riservati.*
*Castel assumes no responsibility for any errors in catalogs, brochures and other material printed or indicated on the Castel.it website. Castel reserves the right to modify its products without notice. All trademarks in this material are the property of Castel. All rights reserved.*