


Product Code

**9150EX/R02**

Connector ATEX  
DIN43650-FormA



**POLYHEDRA**

### Product use

Coils with the new ?FAST LOCK? fixing system, series 9300 and 9320, and coils with gear fixing systems, series 9110, 9120 and 9160.

Fast-on connections type DIN 43650/A for coils in series: 9120, 9160, 9300 and 9320; co-moulded cables for series 9110 coils. Protection rating IP65; IP68 for series 9160 coils coupled with series 9155 connectors.

Available voltages; 24 VAC - 50/60 Hz, 110 VAC - 50/60 Hz, 220/230 VAC - 50/60 Hz, 240 VAC - 50/60 Hz, 380 VAC - 50/60 Hz, 12 VDC, 24 VDC, 27 VDC, 48 VDC.

Connectors in series 9150, normalized DIN 43650, to wire, with IP65 protection rating. Connectors in series 9900, again normalized DIN 43650, pre-wired with various cable lengths, with IP65 protection rating.

Connectors in series 9155, to wire, with IP65/68 protection rating.

### Product details

<b>Grado di protezione</b>	IP 65
<b>Lunghezza cavo [m]</b>	-
<b>Note</b>	Omologazione ATEX per uso in EX zona 2
<b>Confezione n° pz</b>	240

### Notes

(1) Connettore/Raddrizzatore: tensione d'alimentazione 220/230V AC