

## Product Code

# DB308/3S

Solid Core Bi-Flow Filter Drier

3/8" ODS

PS = 50 bar - 680 PSI



## Product use

Bi-flow hermetic filter dryers are designed to be installed on the liquid line of reverse cycle air conditioning systems and heat pumps.

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:

HFCF (R22)

HFC (R134A, R32, R404A, R407C, R410A, R507)

HFO (R1234YF, R1234ZE)

HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)

HC (R290, R600, R600A, R1270)

## Product details

**Codice internazionale** 083S

**Attacchi ODS Ø [in.]** 3/8"

**Attacchi ODS Ø [mm]** -

**Cubatura nominale [cm<sup>3</sup>]** 130

**PS [bar]** 50

**MWP [psi] (1)** 680

**TS [°C] min.** -40

|              |     |
|--------------|-----|
| TS [°C] max. | +80 |
|--------------|-----|

|                  |    |
|------------------|----|
| Confezione n° pz | 25 |
|------------------|----|

## Notes

(1): in conformità a omologazione UL