



Product Code

9120/RD2

Coil Type HM3
24VDC



POLYHEDRA

CLASSIC

Product use

Coils with the new ?FAST LOCK? fixing system, series 9300 and 9320, and coils with gear fixing systems, series 9110, 9120 and 9160.

Fast-on connections type DIN 43650/A for coils in series: 9120, 9160, 9300 and 9320; co-moulded cables for series 9110 coils. Protection rating IP65; IP68 for series 9160 coils coupled with series 9155 connectors. Available voltages; 24 VAC - 50/60 Hz, 110 VAC - 50/60 Hz, 220/230 VAC - 50/60 Hz, 240 VAC - 50/60 Hz, 380 VAC - 50/60 Hz, 12 VDC, 24 VDC, 27 VDC, 48 VDC.

Connectors in series 9150, normalized DIN 43650, to wire, with IP65 protection rating. Connectors in series 9900, again normalized DIN 43650, pre-wired with various cable lengths, with IP65 protection rating.

Connectors in series 9155, to wire, with IP65/68 protection rating.

Product details

Dibujo img(9120_RA6.jpg)

Tipo Bobina HM3 (1)

N° catálogo 9120/RD2

Tensión [V] 24 D.C.

Frecuencia [Hz] -

Potencia [W] 20

CONECTORES Grado de protec 9150/R029900/X66

CONECTORES Grado de protec -

Longitud cable [m]	-
Paquete de n° piezas	24

Notes

(1) bobina con repuesto G9150/R97 (anillo amarillo + tornillo negro + OR)