


## Product Code

# 4411/M42AF

Solid Core Drier Shell  
42mm ODS  
PS = 50 bar - 470 PSI



### Product use

Dryers for the liquid line that allow the replacement of the dryer elements, so-called cartridges. Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:

HCFC (R22)

HFC (R134A, R32, R404A, R407C, R410A, R507)

HFO (R1234YF, R1234ZE)

HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)

HC (R290, R600, R600A, R1270)

### Product details

Dibujo img(4411\_5AF.jpg)

N° catálogo Tapa roscada 4411/M42AF

Conexiones ODS Ø [in.] -

Conexiones ODS Ø [mm] 42

W Ø [mm] 48,3

Tipo cartuchos 4490/A4490/B4490/AA4490/AB4490/BA4490/BB

N° cartuchos 1

Cubicación nominal [cm<sup>3</sup>] 800

PS [bar]	50
MWP [psi] (1)	470
TS [°C] min.	-40
TS [°C] max.	+80
Paquete de n° piezas	1

## Notes

(1) en conformidad con la homologación UL