


Product Code

3315N/7S

Hot Gas Bypass Capacity Reg. - polyhedra

7/8"-22mm ODS

PS = 45 bar



P  **LYHEDRA**

Product use

In refrigeration and air conditioning systems, it is preferable to limit the minimum evaporation pressure during periods of reduced load. Capacity regulators are a solution to these problems as they allow a portion of the hot discharge gas in the high pressure line to bypass directly to the low pressure line, returning the evaporation temperature/pressure to the desired value

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:

HFC (R134A, R32, R404A, R407C, R410A, R507)

HFO (R1234YF, R1234ZE)

HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)

HC (R290, R600, R600A, R1270)

Product details

Dibujo img(3315N_M12S.jpg)

N° catálogo 3315N/7S

Conexiones SAE Flare -

Conexiones Ø ODS [in.] 7/8"

Ø ODS [mm] 22

Campo de regulación [bar] 2 - 7

Kv [m³/h] 1,84

PS [bar]	45
TS [°C] min.	- 40
TS [°C] max.	+ 130
Paquete de n° piezas	8