

## Product Code


# 3340/5S

Condensing Pressure Regulator

5/8"-16mm ODS

PS = 28 bar - 405 PSI

CLASSIC



### Product use

These pressure regulators are designed to limit the liquid flow rate from the condenser to the liquid receiver tank, effectively reducing the exchange surface of the condenser and increasing the condensation pressure. They operate in combination with the differential valve that by-passes the hot gas from the compressor outlet to the liquid receiver tank, increasing the pressure of the liquid in the receiver tank.

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1:

HCFC (R22)

HFC (R134a, R404A, R407C, R410A, R507)

HFO (R1234ze)

HFO + HFC (R448A, R449A, R450A, R452A, R513A, R515A, R515B)

### Product details

Dibujo 

N° catálogo 3340/5S

Conexiones SAE Flare -

Conexiones Ø ODS [in.] 5/8"

Ø ODS [mm] 16

Campo de regulación [bar] 3 - 20

Kv [m<sup>3</sup>/h] 2,7

PS [bar] 28

MWP [psi] (1) 406

TS [°C] min.	- 40
TS [°C] max.	+ 110
Paquete de n° piezas	15

## Notes

(1): en conformidad con la homologación UL