


Product Code

6690NB/M42

3-Ways Valves to be motorized polyhedra

42mm ODS

PS = 50 bar



P  **LYHEDRA**

Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, A3:

HFC (R134A, R32, R404A, R407C, R410A, R507)

HFO (R1234YF, R1234ZE)

HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)

HC (R290, R600, R600A, R1270)

Product details

Dibujo img(6690NB_7.jpg)

N° catálogo (1) (1) 6690NB/M42

Conexiones ODS Ø [in.] -

Conexiones ODS Ø [mm] 42

Orificio Bola Ø [mm] 37

Kv [m³/h] 38,5

PS [bar] 50

MWP [psi] (2) (3)

TS [°C] min. -40

TS [°C] max. +150

Paquete de n° piezas 1

Castel non si assume alcuna responsabilità per eventuali errori nei cataloghi, opuscoli e altro materiale stampato o indicato nel sito Castel.it. Castel si riserva il diritto di modificare i propri prodotti senza preavviso. Tutti i marchi in questo materiale sono di proprietà di Castel. Tutti i diritti riservati.

Castel assumes no responsibility for any errors in catalogs, brochures and other material printed or indicated on the Castel.it website. Castel reserves the right to modify its products without notice. All trademarks in this material are the property of Castel. All rights reserved.

Notes

NB: versiones de flujo proporcional disponibles

(1): completo con adaptador para servomotor con brida de fijación ISO

(2): en conformidad con la homologación UL

(3): no listado por UL