


Product Code

6690NM/11A2

3-Ways Motorized Ball Valve Polyhedra

1.5/8"ODS 24V

PS = 50 bar



P  **LYHEDRA**

Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, A3:

HFC (R134A, R32, R404A, R407C, R410A, R507)

HFO (R1234YF, R1234ZE)

HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)

HC (R290, R600, R600A, R1270)

Product details

Dibujo img(6690NM_11A6.jpg)

N° catálogo (1) 6690NM/11A2

N° catálogo (1)

Conexiones ODS Ø [in.] 1.3/8"

Conexiones ODS Ø [mm] 35

Potencia W Ø [mm] -

P/N Servomotor 9720/RA2

Torque [Nm] 30

Orificio Bola Ø [mm] 28

Kv [m³/h] 20,3

PS [bar] 50

Castel non si assume alcuna responsabilità per eventuali errori nei cataloghi, opuscoli e altro materiale stampato o indicato nel sito Castel.it. Castel si riserva il diritto di modificare i propri prodotti senza preavviso. Tutti i marchi in questo materiale sono di proprietà di Castel. Tutti i diritti riservati.

Castel assumes no responsibility for any errors in catalogs, brochures and other material printed or indicated on the Castel.it website. Castel reserves the right to modify its products without notice. All trademarks in this material are the property of Castel. All rights reserved.

TS [°C] min.	-40
TS [°C] max.	+150
Paquete de n° piezas	1

Notes

NB: versiones de flujo proporcional disponibles
(1): completo con servomotores y placa de montaje