

Product Code

9150N/R69

Orifice Assemblies
07x2028



Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:

- HFC (R134A, R32, R404A, R407C, R410A, R507)
- HFO (R1234YF, R1234ZE)
- HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)
- HC (R290, R600, R600A, R1270)

These valves are only sold in the model without the coil (S suffix), with 9 nozzles assembled for an increasing output from 1 to 22 kW with R410A.

Product details

Dibujo img(9150N_R63.jpg)

N° catálogo 9150N/R69

Tipo orificio 07

Potencialidades nominales (1) [l] 11,26

Potencialidades nominales (1) [l] 24,98

R404A 10,51

R507 10,51

R407C 14,66

R410A 17,22

R1234ze 8,84

R1234yf 8,30

R448A 14,03

R449A	13,77
R450A	9,88
R452A	10,88
R452B	19,42
R454A	14,21
R454B	19,61
R454C	12,13
R513A	9,55
R515A	8,51
R515B	8,47
R290	15,17
R600	9,63
R600a	9,95
R1270	16,98
Paquete de n° piezas	180

Notes

(1) Las potencialidades nominales se refieren a:

- Temperatura de evaporación $T_{evap} = + 5 \text{ °C}$
- Temperatura de condensación $T_{cond} = + 32 \text{ °C}$
- Temperatura del líquido en la entrada de la válvula $T_{liq} = + 28 \text{ °C}$