


Product Code

**1078N/M12S**

Solenoid Valve  
12mm ODS w/o Coil  
PS = 50 bar



**P**  **LYHEDRA**

### Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:  
HFC (R134A, R32, R404A, R407C, R410A, R507)  
HFO (R1234YF, R1234ZE)  
HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)  
HC (R290, R600, R600A, R1270)

These valves are sold in both the version without the coil (S suffix) and the version with the coil (A6 suffix for coils at 220 VAC).

### Product details

**Principio de funcionamiento** Servomandode membrana

**Dibujo** img(1078N\_4S.jpg)

**N° catálogo** 1078N/M12S

**Tipo Bobina (1)** HF2HF3HF4HM2HM3HM4CM2

**Conexiones ODS Ø [in.]** -

**Conexiones ODS Ø [mm]** 12

**Kv [m³/h]** 2,2

**PS [bar]** 50

**TS [°C] min.** -40

TS [°C] max.	+120
Paquete de n° piezas	17

## Notes

(1) bobinas que pueden montarse en las válvulas