



Product Code

1328N/3S020

Pulse Solenoid Valve

3/8"ODS w/o Coil

PS = 50 bar

POLYHEDRA

Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:
HFC (R134A, R32, R404A, R407C, R410A, R507)
HFO (R1234YF, R1234ZE)
HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)
HC (R290, R600, R600A, R1270)

These valves are sold in both the version without the coil (S suffix) and the version with the coil (A6 suffix for coils at 220 VAC).

Product details

Principio de funcionamiento	Acción directa
Dibujo	img(1328N_2S.jpg)
N° catálogo	1328N/3S020
Tipo Bobina (1)	HF2HF3HF4HM2HM3HM4CM2
Conexiones ODS Ø [in.]	3/8"
Conexiones ODS Ø [mm]	-
Kv [m³/h]	0,15
PS [bar]	50
TS [°C] (2) min.	-40

TS [°C] (2) max.	+150
------------------	------

Paquete de n° piezas	24
----------------------	----

Notes

(#) : para by-pass de gas caliente, inyección de líquido, línea de aceite

(1) : bobinas que pueden montarse en las válvulas

(2) : para usar en la línea de aceite TS = -10 /+ 70 ° C