


## Product Code

# 9100EX/RA7

Coil Type HM2 ATEX  
240V 50/60Hz



### Product use

Coils with the new ?FAST LOCK? fixing system, series 9300 and 9320, and coils with gear fixing systems, series 9110, 9120 and 9160.

Fast-on connections type DIN 43650/A for coils in series: 9120, 9160, 9300 and 9320; co-moulded cables for series 9110 coils. Protection rating IP65; IP68 for series 9160 coils coupled with series 9155 connectors.

Available voltages; 24 VAC - 50/60 Hz, 110 VAC - 50/60 Hz, 220/230 VAC - 50/60 Hz, 240 VAC - 50/60 Hz, 380 VAC - 50/60 Hz, 12 VDC, 24 VDC, 27 VDC, 48 VDC.

Connectors in series 9150, normalized DIN 43650, to wire, with IP65 protection rating. Connectors in series 9900, again normalized DIN 43650, pre-wired with various cable lengths, with IP65 protection rating.

Connectors in series 9155, to wire, with IP65/68 protection rating.

### Product details

**Coil Type** HM2

**Voltage [V]** 240

**Frequency [Hz]** 50/60

**Power [W]** 8

**Connections Degree of protectic** 9150EX/R02

**Connections Degree of protectic** -

**Note** ATEX approval for use in EX Zone 2--- Spare part G9151/R14 (light blue nut + b

**Cable length [m]** -

**Package Pcs.** 90

## Notes

(1): coil with spare part G9150/R97 (yellow nut + black screw + OR)