



Product Code

9900/X87

3-Ways Manifold

-

PS = 45 bar

Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:

- HCFC (R22)
- HFC (R134a, R32, R404A, R407C, R410A, R507)
- HFO and HFO/HFC blends (R1234ze, R1234yf, R448A, R449A, R450A, R452A, R513A, R515A, R515B)
- HC (R290, R600, R600a, R1270)
- R744

Product details

Input connection SAE Flare	1/4"
Lateral output connections	2 x 1/4" SAE M
Longitudinal output connection:	1 x 1/8" SAE F
Lenght [mm]	132
PS [bar]	45
TS [°C] min.	-40
TS [°C] max.	+150
Fluids	HC-HFC-HFO-R744
Package pcs	25

Notes

(1): including fixation support 2xM10

(2): including fixation support 4xM4 and hermetic valve

Castel non si assume alcuna responsabilità per eventuali errori nei cataloghi, opuscoli e altro materiale stampato o indicato nel sito Castel.it. Castel si riserva il diritto di modificare i propri prodotti senza preavviso. Tutti i marchi in questo materiale sono di proprietà di Castel. Tutti i diritti riservati.

Castel assumes no responsibility for any errors in catalogs, brochures and other material printed or indicated on the Castel.it website. Castel reserves the right to modify its products without notice. All trademarks in this material are the property of Castel. All rights reserved.