



## Product Code

# 1058N/7A6

Solenoid Valve

7/8"-22mm ODS 220-230V

PS = 50 bar

**P**  **LYHEDRA**

### Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:

- HFC (R134A, R32, R404A, R407C, R410A, R507)
- HFO (R1234YF, R1234ZE)
- HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)
- HC (R290, R600, R600A, R1270)

These valves are sold in both the version without the coil (S suffix) and the version with the coil (A6 suffix for coils at 220 VAC).

### Product details

|                                |                       |
|--------------------------------|-----------------------|
| <b>Operating principle</b>     | Piston pilot operated |
| <b>Coil Type (1)</b>           | HF2                   |
| <b>Connections ODS Ø [in.]</b> | 7/8"                  |
| <b>Connections ODS Ø [mm]</b>  | 22                    |
| <b>Kv [m<sup>3</sup>/h]</b>    | 5,7                   |
| <b>PS [bar]</b>                | 50                    |
| <b>TS [°C] min.</b>            | -40                   |
| <b>TS [°C] max.</b>            | +130                  |
| <b>Package Pcs.</b>            | 14                    |

## Notes

(1) : coils mounted on the valves