



## Product Code

# 1348N/5S125

Solenoid Valve  
5/8"-16mm ODS w/o Coil  
PS = 50 bar

**P**  **LYHEDRA**

### Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:  
HFC (R134A, R32, R404A, R407C, R410A, R507)  
HFO (R1234YF, R1234ZE)  
HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)  
HC (R290, R600, R600A, R1270)

These valves are sold in both the version without the coil (S suffix) and the version with the coil (A6 suffix for coils at 220 VAC).

### Product details

<b>Principe de fonctionnement</b>	Servocommande à piston
<b>Type bobine (1)</b>	HF2HF3HF4HM2HM3HM4CM2
<b>Raccords ODS Ø [in.]</b>	5/8"
<b>Raccords ODS Ø [mm]</b>	16
<b>Kv [m<sup>3</sup>/h]</b>	3
<b>PS [bar]</b>	50
<b>TS [°C] (2) min.</b>	-40
<b>TS [°C] (2) max.</b>	+150
<b>Emballage</b>	14

## Notes

(#): pour la dérivation de gaz chaud, injection de liquide, conduite d'huile

(1) : bobines qui peuvent être montés sur les vannes

(2): pour utilisation sur la conduite d'huile TS = -10 / + 70 ° C