

Product Code

9150N/R66

Orifice Assemblies
04x2028



Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:

- HFC (R134A, R32, R404A, R407C, R410A, R507)
- HFO (R1234YF, R1234ZE)
- HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)
- HC (R290, R600, R600A, R1270)

These valves are only sold in the model without the coil (S suffix), with 9 nozzles assembled for an increasing output from 1 to 22 kW with R410A.

Product details

Type d'orifice 04

Capacités nominales (1) [kW] R13,01

Capacités nominales (1) [kW] R2 6,68

R404A 2,81

R507 2,81

R407C 3,92

R410A 4,60

R1234ze 2,36

R1234yf 2,22

R448A 3,75

R449A 3,68

R450A 2,64

R452A	2,91
R452B	5,19
R454A	3,80
R454B	5,24
R454C	3,24
R513A	2,55
R515A	2,27
R515B	2,26
R290	4,05
R600	2,57
R600a	2,66
R1270	4,54
Emballage	180

Notes

(1) Les capacités nominales se basent sur :

- Température d'évaporation $T_{\text{evap}} = +5 \text{ °C}$
- Température de condensation $T_{\text{cond}} = +32 \text{ °C}$
- Température du liquide frigorigène en amont du détendeur $T_{\text{liq}} = +28 \text{ °C}$