


Product Code

9150/R78

Orifice Assemblies
08x2028

CLASSIC



Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1:

HCFC (R22)

HFC (R134a, R404A, R407C, R410A, R507)

HFO (R1234ze)

HFO + HFC (R448A, R449A, R450A, R452A, R513A,
R515A, R515B)

These valves are only sold in the model without the coil (S suffix), with 9 nozzles assembled for an increasing output from 1 to 22 kW with R410A.

Product details

Type d'orifice 08

Capacités nominales (1) [kW] R1 13,57

Capacités nominales (1) [kW] R2 17,29

R404A 12,66

R507 12,66

R407C 17,67

R410A 20,75

R1234ze 10,66

R448A 16,91

R449A 16,60

Castel non si assume alcuna responsabilità per eventuali errori nei cataloghi, opuscoli e altro materiale stampato o indicato nel sito Castel.it. Castel si riserva il diritto di modificare i propri prodotti senza preavviso. Tutti i marchi in questo materiale sono di proprietà di Castel. Tutti i diritti riservati.

Castel assumes no responsibility for any errors in catalogs, brochures and other material printed or indicated on the Castel.it website. Castel reserves the right to modify its products without notice. All trademarks in this material are the property of Castel. All rights reserved.

R450A	11,91
R452A	13,11
R513A	11,51
R515A	10,25
R515B	10,21
Emballage	180

Notes

(1) Les capacités nominales se basent sur :

- Température d'évaporation $T_{\text{evap}} = +5 \text{ °C}$
- Température de condensation $T_{\text{cond}} = +32 \text{ °C}$
- Température du liquide frigorigène en amont du détendeur $T_{\text{liq}} = +28 \text{ °C}$