



Product Code

1079EX/11A6

Solenoid Valve ATEX
1.3/8"-35mm ODS w/o Coil
PS = 50 bar

P  **LYHEDRA**

Product use

Solenoid valves with the "EX" suffix are compliant with the ESR of Directive 2014/34/EU "ATEX". This equipment is suitable for use on refrigeration systems located in areas classified as "Zone 2" risk of explosion, according to the definition in Annex I of Directive 1999/92/EC.

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:

HFC (R134A, R32, R404A, R407C, R410A, R507)

HFO (R1234YF, R1234ZE)

HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)

HC (R290, R600, R600A, R1270)

These valves are only sold in the model with the ATEX certified coil (A6 suffix).

Product details

Funtionsprinzip Membranantrieb

Spulentyp (1) HM2(EX)

Anschlüsse ODS Ø [in.] 1.3/8"

Anschlüsse ODS Ø [mm] 35

Kv [m³/h] 10

PS [bar] 50

TS [°C] min. -40

TS [°C] max. +120

Notes

(1): An den Ventilen montierte Spulen