

Product Code

9150N/R66

Orifice Assemblies
04x2028



Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:
 HFC (R134A, R32, R404A, R407C, R410A, R507)
 HFO (R1234YF, R1234ZE)
 HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)
 HC (R290, R600, R600A, R1270)

These valves are only sold in the model without the coil (S suffix), with 9 nozzles assembled for an increasing output from 1 to 22 kW with R410A.

Product details

Düseneinsatz Typ	04
Nennleistungen (1) [kW] R134a	3,01
Nennleistungen (1) [kW] R32	6,68
R404A	2,81
R507	2,81
R407C	3,92
R410A	4,60
R1234ze	2,36
R1234yf	2,22
R448A	3,75
R449A	3,68
R450A	2,64

R452A	2,91
R452B	5,19
R454A	3,80
R454B	5,24
R454C	3,24
R513A	2,55
R515A	2,27
R515B	2,26
R290	4,05
R600	2,57
R600a	2,66
R1270	4,54
Verpackung	180

Notes

(1) Nennleistungen basieren auf:

- Verdampfungstemperatur $T_{\text{verd}} = +5 \text{ }^{\circ}\text{C}$
- Kondensationstemperatur $T_{\text{kond}} = +32 \text{ }^{\circ}\text{C}$
- Temperatur des flüssigen Kältemittels vor dem Ventil $T_{\text{flü}} = +28 \text{ }^{\circ}\text{C}$