


Product Code

9151N/R61

Orifice Assemblies
00x2028N



Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:

- HFC (R134A, R32, R404A, R407C, R410A, R507)
- HFO (R1234YF, R1234ZE)
- HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)
- HC (R290, R600, R600A, R1270)

These valves are only sold in the model without the coil (S suffix), with 9 nozzles assembled for an increasing output from 1 to 22 kW with R410A.

Product details

Düseneinsatz Typ	00
Nennleistungen (1) [kW] R134a	0,22
Nennleistungen (1) [kW] R32	0,49
R404A	0,21
R507	0,21
R407C	0,29
R410A	0,34
R1234ze	0,17
R1234yf	0,16
R448A	0,27
R449A	0,27
R450A	0,19

R452A	0,21
R452B	0,38
R454A	0,28
R454B	0,38
R454C	0,24
R513A	0,19
R515A	0,17
R515B	0,17
R290	0,30
R600	0,19
R600a	0,19
R1270	0,33
Verpackung	180

Notes

(1) Nennleistungen basieren auf:

- Verdampfungstemperatur $T_{\text{verd}} = +5 \text{ °C}$
- Kondensationstemperatur $T_{\text{kond}} = +32 \text{ °C}$
- Temperatur des flüssigen Kältemittels vor dem Ventil $T_{\text{flü}} = +28 \text{ °C}$