



Product Code

1348N/M12S125

Solenoid Valve
12mm ODS w/o Coil
PS = 50 bar

P  **LYHEDRA**

Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:
HFC (R134A, R32, R404A, R407C, R410A, R507)
HFO (R1234YF, R1234ZE)
HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)
HC (R290, R600, R600A, R1270)

These valves are sold in both the version without the coil (S suffix) and the version with the coil (A6 suffix for coils at 220 VAC).

Product details

| | |
|-------------------------------|-----------------------|
| Funtionsprinzip | Kolbenantrieb |
| Spulentyp (1) | HF2HF3HF4HM2HM3HM4CM2 |
| Anschlüsse ODS Ø [in.] | - |
| Anschlüsse ODS Ø [mm] | 12 |
| Kv [m³/h] | 2,4 |
| PS [bar] | 50 |
| TS [°C] (2) min. | -40 |
| TS [°C] (2) max. | +150 |
| Verpackung | 14 |

Notes

(#): für Heißgas-Bypass, Flüssigkeitseinspritzung, Ölleitung

(1) : Spulen, die an den Ventilen montiert werden können

(2): für den Einsatz in der Ölleitung TS = -10 / + 70 ° C