



Product Code

9720/RA2

Electrical Actuator
30Nm 24V 50Hz

GO GREEN

BY THE WAY WE DECIDE

POLYHEDRA

CLASSIC

Product use

Actuators can be assembled, using suitable flanged adaptors, to 2-ways ball valves and to manual 3-ways ball valves. They are assembled directly on the motorized 3-ways ball valves. Once this coupling has been performed, the valve can be opened or closed remotely. Alternatively, the actuator can be excluded and the valve can be operated manually.

Castel manufacturers actuator with a variety of operational characteristics: they are manufactured with a synthetic, self-extinguishing housing that covers the motor, the control and cut-out electronics based on the gear reducer torque and the self centring fixing system of the valve rod.

In the event of a power outage to the actuator, the gear reducer can be disengaged using the specific lever, to permit manual use of the valve.

Furthermore, auxiliary contacts for switching are available for remote control of the valve status.

Product details

Desenho 

N° catálogo 9720/RA2

N° catálogo (1)

Tensão [V] 24

Frequência [Hz] 50/60

Potência [W]	2,4
Grau de proteção	IP 54
Ângulo de manobra	90°
Torque [Nm]	30
Tempo de marcha [sec]	120
Temperatura ambiente [°C] min.	-20
Temperatura ambiente [°C] max.	+50
Adequado para válvulas esféricas: veja os acoplamentos indicados na tabela DIAGRAMA DE ACOPLAMENTO	
Embalagem	1

Notes

- (1) Conexiones eléctricas: salida en conmutación de 2 puntos (abierto/cerrado) o bien salida en continua (0 ÷ 10V)
- (2) Conexiones eléctricas: Salida en conmutación de 2 puntos (abierto/cerrado)
- (3) Conexiones eléctricas: salida en continua (0 ÷ 10V)