



Product Code

1328N/3S020

Pulse Solenoid Valve
3/8" ODS w/o Coil
PS = 50 bar

P  **LYHEDRA**

Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:
HFC (R134A, R32, R404A, R407C, R410A, R507)
HFO (R1234YF, R1234ZE)
HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)
HC (R290, R600, R600A, R1270)

These valves are sold in both the version without the coil (S suffix) and the version with the coil (A6 suffix for coils at 220 VAC).

Product details

Princípio de funcionamento	Ação direta
Desenho	img(1328N_2S.jpg)
N° catálogo	1328N/3S020
Tipo de Bobina (1)	HF2HF3HF4HM2HM3HM4CM2
Ligações ODS Ø [in.]	3/8"
Ligações ODS Ø [mm]	-
Kv [m³/h]	0,15
PS [bar]	50
TS [°C] (2) min.	-40

TS [°C] (2) max.	+150
------------------	------

Embalagem	24
-----------	----

Notes

(#) : para by-pass de gás quente, de injeção de líquido, linha de óleo

(1) : bobinas que podem ser montadas nas válvulas

(2) : para uso na linha de óleo TS = -10 /+ 70 ° C