



Product Code

**1198N/7S**

Solenoid Valve  
7/8"-22mm ODS w/o Coil  
PS = 50 bar

**P**  **LYHEDRA**

## Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:  
HFC (R134A, R32, R404A, R407C, R410A, R507)  
HFO (R1234YF, R1234ZE)  
HFO + HFC (R448A, R449A, R450A, R452A, R452B, R454A, R454B, R454C, R455A, R513A, R515A, R515B)  
HC (R290, R600, R600A, R1270)

These valves are exclusively sold in the model without coil (S suffix).

## Product details

**Princípio de funcionamento** Servocomando commembrana

**Desenho** img(1198N\_5S.jpg)

**N° catálogo** 1198N/7S

**Tipo de Bobina (1)** HM3

**Ligações ODS Ø [in.]** 7/8"

**Ligações ODS Ø [mm]** 22

**Kv [m<sup>3</sup>/h]** 5,7

**PS [bar]** 50

**TS [°C] min.** -40

**TS [°C] max.** +120

## Notes

As válvulas NA foram projetadas para o funcionamento com bobina em corrente contínua.  
Para aplicações com alimentação de 220/230 V CA utilizar a bobina 9120/RD6 com o conector 9150/R45  
(1) : Bobinas que podem ser montadas nas válvulas